

2

1

POWER REQUIREMENTS	AC 120 v @ 60Hz		
	BATTERY BACKUP		4X AA+ BATTERY
LAMPS	LED 5v RGB		WS2811 DIODES
	IR REMOTE CONTROLLER		
	CUSTOMIZABLE WIFI APP		
PROFLAME II SYSTEM	5 LEVELS OF FLAME INTENSITY		
	REMOTE CONTROLLED IGNITION		
	VENTED CONFIGURATION ONLY		
GLOWFIRE LOG SPECIES	LDBT-WD48	WESTERN DRIFTWOOD	
HEATING OUTPUT	MAXIMUM HEAT	62,000 BTU/hr	18.17 kW
	MINIMUM HEAT (EN)	45,000 BTU/hr	13.19 kW
	MINIMUM HEAT (EP)	30,000 BTU/hr	8.79 kW

47.75

14.75

LEFT VIEW

POWER OUT

RIGHT VIEW

GAS OUT

6.10

NOTE:  
EN- NATURAL GAS  
EP- PROPANE  
**MUST ADD GLOWFIRE LOGS**

MINIMUM FIRE BOX DIM. (INCHES)		
WIDTH	DEPTH	HEIGHT
48	15	20

TITLE:  
BEDROCK TRADITIONAL  
LINEAR DROP IN BURNER  
LDBT48-EN, LDBT48-EP

SIZE	DWG. NO.	REV
<b>A</b>	LDBT48-XX	B
SCALE: N/A WEIGHT:		SHEET 1 OF 1