

2

1

POWER REQUIREMENTS	AC 120 v @ 60Hz		
	BATTERY BACKUP		4X AA+ BATTERY
LAMPS	LED 5v RGB		WS2811 DIODES
	IR REMOTE CONTROLLER		
	CUSTOMIZABLE WIFI APP		
PROFLAME II SYSTEM	5 LEVELS OF FLAME INTENSITY		
	REMOTE CONTROLLED IGNITION		
	VENTED CONFIGURATION ONLY		
GLOWFIRE LOG SPECIES	LDBT-DW96	WESTERN DRIFTWOOD	
HEATING OUTPUT	MAXIMUM HEAT (EN)	120,000 BTU/hr	35.17 kW
	MINIMUM HEAT (EN)	80,000 BTU/hr	23.45 kW
	MAXIMUM HEAT (EP)	120,000 BTU/hr	35.17 kW
	MINIMUM HEAT (EP)	60,000 BTU/hr	17.58 kW

95.75

14.75

LEFT VIEW

RIGHT VIEW

POWER OUT

GAS OUT

6.11

NOTE:
EN- NATURAL GAS
EP- PROPANE
MUST ADD GLOWFIRE LOGS



MINIMUM FIRE BOX DIM. (INCHES)		
WIDTH	DEPTH	HEIGHT
96	15	20

GRAND CANYON GAS LOGS

TITLE:
BEDROCK TRADITIONAL
LINEAR DROP IN BURNER
LDBT96-EN, LDBT96-EP

SIZE	DWG. NO.	REV
A	LDBT96-XX	C

SCALE: N/A	WEIGHT:	SHEET 1 OF 1
------------	---------	--------------